



ARDON®
WORKWEAR
& OUTDOOR

ARDON® PETRAX DOUBLE

MULTIFUNCTIONAL HANDLING IN DRY AND WET ENVIRONMENTS
WITH THE POSSIBILITY OF HEAT PROTECTION



TECHNICAL DATA



EN 388: 2016



EN 407: 2004



PG020 228259
OETI



STANDARD
100



ARDON®
WORKWEAR
& OUTDOOR

ARDON® PETRAX DOUBLE

MULTIFUNCTIONAL HANDLING IN DRY AND WET ENVIRONMENTS
WITH THE POSSIBILITY OF HEAT PROTECTION

CODE A8107

MATERIAL

Lining 15G polyester
Coating ¾ latex (red) + ½ latex foam (black)
Thickness 1,4 mm (in palm)

SIZE(S) 7 / S – 11 / 2XL

UNIT pair

PACKING


Units in carton 120 pairs
Units in polybag 12 pairs
Retail packaging sales label, size 10 / XL also without sales label

DIMENSIONS

	5	6	7	8	9	10	11	12
Carton H x W x D (cm)	-	-	43x27x34	43x27x34	43x27x34	43x28x35	43x28x35	-
Carton (cbm)	-	-	0,0395	0,0395	0,0395	0,0421	0,0421	-

WEIGHT

	5	6	7	8	9	10	11	12
Carton (kg)	-	-	8,60	9,50	10,2	10,9	11,6	-
Unit (g)	-	-	55,0	62,0	68,0	74,0	80,0	-



Size chart (cm)

	5	6	7	8	9	10	11	12
Total length (A)	-	-	23,0	24,0	25,0	26,0	27,0	-
Cuff length (B)	-	-	7,10	7,30	7,50	7,70	7,90	-
Cuff width (C)	-	-	7,80	8,00	8,20	8,40	8,60	-
Palm width (D)	-	-	9,80	10,3	11,0	11,2	11,5	-

Tolerance (A) ± 0,50 (cm)

Tolerance (B) ± 0,70 (cm)

Tolerance (C) ± 0,70 (cm)

Tolerance (D) ± 0,70 (cm)

DESCRIPTION

Comfortable knit with double latex dipping, waterproof and with a secure grip.

TECHNICAL DATA



ARDON®
WORKWEAR
& OUTDOOR


STANDARDS

(EU) 2016/425


EN ISO 21420:2020 + A1:2024 Protective gloves – general requirements and test methods

EN 388:2016 + A1:2018 Protective gloves against mechanical risks

EN 407:2020 Protective gloves against heat and/or fire

PROTECTION LEVELS		LVL	score	unit
 <p>EN 388</p>	MECHANICAL RISKS			
	abrasion resistance	2	500 – 2.000	cykles
	cut resistance	1	1,2 – 2,5	index
	tearing resistance	4	> 75	N
	puncture resistance	1	20 – 60	N
	cut resistance acc. to ISO	X	not measured	N

EN 407:2004 Protective gloves against heat or flame

PROTECTION LEVELS		LVL	score
 <p>EN 407</p>	THERMAL RISKS		
	resistance to burning	X	not measured
	resistance to contact heat	2	250°C for 15s
	resistance to convectional heat	X	not measured
	resistance to radiant heat	X	not measured
	resistance to small drops of molten metals	X	not measured
	resistance to large drops of molten metals	X	not measured

SPECIAL FEATURES

- functional double dipping:
 - the base layer of smooth latex acts as a barrier against liquids
 - outer layer of latex foam allows a secure grip (even on wet objects)
- for work in both dry and wet environments, for example with loose mixtures with water (building mixtures, mortar, paints, etc.)
- protection against heat up to 150 ° C (according to certification up to 250 ° C for 15 seconds, but we generally do not recommend exposure to temperatures higher than 150 ° C, during which latex secondary vulcanizes and heats up)
- mandatory information on inner label = ARDON® design
- each pairs in each size is retail ready packed, size 10 / XL also without sales label
- all PETRAX DOUBLE gloves are certified according to **OEKO-TEX® STANDARD 100** and compliant with the **REACH regulation**.

TECHNICAL DATA



ARDON[®]
WORKWEAR
& OUTDOOR

Retail packaging (with sales label)

A8107/07-SPE

A8107/08-SPE

A8107/09-SPE

A8107/10-SPE

A8107/11-SPE

Basic packaging (without sales label)

A8107/10

EAN

8592390012814

8592390075611

8592390075628

8592390075635

8592390041685

8592390373823

TECHNICAL DATA



ARDON®
WORKWEAR
& OUTDOOR



TECHNICAL DATA