



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

# ARDON® SOFTEX HIGH S1P

SAFETY SHOES



DRY AIR



DEFUSE  
CONTROL



WASH-FRIENDLY

TECHNICAL SHEET



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

# ARDON® SOFTEX HIGH S1P

SAFETY SHOES

**ARTICLE** G3404

**COLOUR**  
**MATERIAL**

Upper  
 Lining  
 Sole  
 Toe cap  
 Plate  
 Insole

**black/yellow**

textilie typu SOFTSHELL

MESH laminated breathable fabric

PU/PU, two-component spray coating, oil resistant, anti-static, antislip steel 604

steel

ANATOMIC GEL - anatomically shaped from PU foam with a gel cushioning in the heel area

**SIZE**

38-50

**UNIT**

pair

**PACKAGE**

Units in a carton

10 pairs

Units in a box

1 pair

**DIMENSIONS**

Carton H x W x D  
 (cm)

38-41

57x 33 x 38,5

42-45

59,5x 35,5 x 40,5

46-50

62x38x41,5

Carton (cbm)

0,0724

0,0855

0,0978

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	-	-	248	255	262	270	276	283	290	297	304	310	317	323	330	-
Foot length cm	-	-	-	23,8	24,5	25,2	26,0	26,6	27,3	28,0	28,7	29,4	30,0	30,7	31,3	32,0	-

**DESCRIPTION**

Safety softshell low shoe in sporty design. The ANATOMIC GEL insole with a cushioning gel element in the heel takes care of the increased comfort of the shoes. The shoes are equipped with a steel toe and an anti-puncture insole. The stable polyurethane sole made by direct spraying provides the highest level of anti-slip properties.

TECHNICAL SHEET



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

## NORMS

(EU) 2016/425

EN ISO 20345:2022+A1:2024

Personal protective equipment – Safety footwear

Category

S1 P FO SR

### Categories

### EN ISO 20345

E - energy absorption in the heel area

✓



FO - resistance to oils and fuels

✓



A - antistatic footwear

✓



SR - resistance to slipping on ceramic floor tiles with SLS  
and on steel floors with glycerin

✓



WPA – water penetration and absorption



Safety toe cap for toe protection

✓



P - resistance to punctures (protective insole)

✓



The shoes do not contain metal parts



HRO - resistance to contact heat up to 300 °C



HI-insulation of the bottom of the shoe against heat



CI-insulation of the bottom of the shoe against the cold



Splatters of molten metal



ESD – shoe protects against electrostatic discharge and can  
be used on EPA premises



-

-

-

TECHNICAL SHEET



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

<b>CODE</b>	<b>EAN</b>	<b>CARTON WEIGHT (KG)</b>	<b>UNIT WEIGHT (KG)</b>
G3404/38	8592390168979	12.3	1.23
G3404/39	8592390168986	12.6	1.26
G3404/40	8592390168993	12.8	1.28
G3404/41	8592390169006	13.1	1.31
G3404/42	8592390169013	13.5	1.35
G3404/43	8592390169020	14.0	1.40
G3404/44	8592390169037	14.5	1.45
G3404/45	8592390169044	15.0	1.50
G3404/46	8592390169051	15.7	1.57
G3404/47	8592390169068	16.2	1.62
G3404/48	8592390169075	16.7	1.67
G3404/49	8592390169082	17.1	1.71
G3404/50	8592390169099	17.8	1.78



TECHNICAL SHEET



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**



TECHNICAL SHEET



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**



TECHNICAL SHEET