



ARDON[®]
WORKWEAR
& OUTDOOR

ARDON[®] 4EAR P201

CORDED EARPLUGS



TECHNICAL DATA SHEET



ARDON[®]
WORKWEAR
& **OUTDOOR**

ARDON[®] EAR P201

CORDED EARPLUGS

ARTICLE NO. C4003

MATERIAL Thermoplastic rubber

COLOUR yellow

SNR 30 dB



DESCRIPTION

Pre-moulded reusable earplugs, three flanges, with a connection string, come in a box with a loop.

ATTENUATION:

SNR: 29,6 dB

High: 27,1

Medium: 28,1

Low: 28,3

Frequency (Hz)	125	250	500	1000	2000	4000	8000
Mean Attenuation (dB)	33,1	32,4	33,8	31,7	29,3	39,8	42,2
Standard Deviation (dB)	4,9	4,7	4,2	3,4	4,8	5,4	3,8
APV (db)	28,2	27,7	29,6	28,2	24,5	33,5	38,3



ARDON®
WORKWEAR
& OUTDOOR

STANDARDS

This personal protective equipment is in conformity with these harmonized European Standards:

EN 352-2:2020: Hearing protectors - General requirements - Part 2: Earplugs

Certified by Notified Body No. 2797, BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands Certificate No. CE 821496, issued on 19 of February 2025

PIECES IN CARTON	1000 ks
PIECES IN A BOX:	100 ks
UNIT PACKING (polybag):	1 ks
WEIGHT OF A CARTON	17,3 kg
DIMENSIONS OF A CARTON	0,125m ³

Earplugs must be inserted correctly to effectively reduce noise. Sudden or rapid removal from the ear canal can damage the eardrum. They are designed for repeated use and must be molded before use. They must not be used where there is a risk of the cord getting caught during use.

This product may be adversely affected by certain chemical substances. Although hearing protectors are recommended for protection against the harmful effects of impulse noise, the SNR value is based on attenuation in continuous noise and may not be an accurate indicator of the protection achievable in impulse noise, for example shooting. .