

Product leaflet

Product	Model No.	Ordering No.
Powered air purifying respirator	SR 500	H06-0112

Product Description

The SR 500 is a battery-powered fan that, together with a filter and an approved head top, is included in the Sundström fan-assisted respiratory protective device systems. The SR 500 can be used as an alternative to filter respirators in all situations in which these are recommended. This applies particularly to work that is hard, warm or of long duration.

The human interface may consist of a hood, face shield, half mask or full face mask. The fan is equipped with a filter, and the filtered air is fed through a hose to the human interface. The pressure then generated prevents surrounding pollutants from penetrating into the mask.

The characteristics of the SR 500 are as follows:

The battery is of lithium-ion type • Two battery alternatives, i.e. STD (Standard 2.25 Ah) and HD (Heavy Duty 3.5 Ah) • The charging time for the Standard battery is around 2 hours and for the Heavy Duty battery, about 3 hours • Battery capacity indicator • Equipped with two filters/combined filters • Operating time of up to 11 hours • The same control is used for starting, stopping and selection of operating status • Display with symbols • Equipped with automatic air flow control with compensation for air pressure and temperature • Can be used together with hoods SR 520, SR 530, SR 561, SR 562, SR 601, SR 602, SR 604, face shield SR 570, welding shield/face shield SR 574/SR 570, half mask SR 900, full face mask SR 200, welding shield SR 592, helmet with visor SR 575, SR 580 or welding shield/helmet with visor SR 574/SR 575, SR 584/SR 580.

Electronics ingress protection is approved in IP class IP67 according to IEC / EN 60529.

The SR 500 is also available in an explosion-protected version designated the SR 500 EX for use in a potentially explosive atmosphere. See the separate product leaflet.

Technical specification

	SR 500	EN 12941:1998 + A2:2008	EN12942:1998 + A2:2008
Air flow, min/max	175/240 l/min	≥ 120 l/min	-
STD-battery/HD-Battery	14,4 V 2,25 Ah/3,5 Ah	-	-
Operating times at 175/240 l/min:			
P3, STD-battery	7 h/4 h	≥ 4 h	≥ 4 h
P3, HD- battery	11 h/6 h	≥ 4 h	≥ 4 h
Weight with STD-battery and P3 filter	≈ 1 650 g	≤ 3,500 g	≤ 3,500 g
Service conditions	-10 °C to +55 °C, < 90 % RH, 600 to 1200 hPa	-	-
Storage conditions	-20 °C to +40 °C, < 90 % RH	-	-
Low flow warning level	< 175 l/min	≤ 175 l/min	≤ 175 l/min
Assigned Protection Factor¹: SR 520, SR 530, SR 561, SR 562, SR 570, SR 574, SR 575, SR 580, SR 584, SR 592, SR 601, SR 602, SR 604	40 (TH3)	-	-
Assigned Protection Factor¹ SR 200, SR 900	40 (TM3)	-	-
Nominal Protection Factor² SR 520, SR 530, SR 561, SR 562, SR 570, SR 574, SR 575, SR 580, SR 584, SR 592, SR 601, SR 602, SR 604	500 (TH3)	-	-
Nominal Protection Factor² SR 200, SR 900	2000 (TM3)	-	-
Approvals	EN 12941:1998 + A2:2008 EN 12942:1998 + A2:2008	-	-


1) Specified in BS EN 529 and applies generally to all approved fan-assisted respiratory protective devices, regardless of the test results.

2) According to EN 529:2005.



Sundström Safety AB
Tel: +46 10 484 87 00
Västergatan 4
SE-341 50 Lagan

Sundström
www.srsafety.com



Head-tops, spare parts and accessories

Item

No. Part

Ordering No.

- | | |
|--|----------|
| 1. Hood SR 520 M/L | H06-0212 |
| 1. Hood SR 520 S/M | H06-0312 |
| 2. Hood SR 530 | H06-0412 |
| 3. Face shield SR 570 | H06-6512 |
| 4. Welding shield/Face shield SR 574/SR 570 | H06-6110 |
| 5. Full face mask SR 200, PC visor | H01-1212 |
| 5. Full face mask SR 200, glass visor | H01-1312 |
| 6. Full face mask SR 200 Airline, PC visor | H03-1012 |
| 6. Full face mask SR 200 Airline, glass visor | H03-1212 |
| 7. PU hose SR 550 for SR 200 | T01-1216 |
| 7. Rubber hose SR 551 for SR 200 | T01-1218 |
| 8. SR 900 S | H01-3012 |
| 8. SR 900 M | H01-3112 |
| 8. SR 900 L | H01-3212 |
| 9. Hose SR 951 | T01-3003 |
| 10. Twin hose SR 952 | R01-3009 |
| 11. Hood SR 561 | H06-5012 |
| 12. Hood SR 562 | H06-5112 |
| 13. Welding shield/Helmet with visor SR 592 | H06-4412 |
| 14. Helmet with visor SR 580 | H06-8012 |
| 15. Welding shield/Helmet with visor SR 584/SR 580 | H06-8310 |
| 16. Hood SR 601 | H06-5412 |
| 16. Hood SR 602 | H06-5512 |
| 16. Hood SR 604 | H06-5912 |
| 17. Helmet with visor SR 575 | H06-9010 |
| 18. Welding shield/Helmet with visor SR 574/SR 575 | H06-9310 |
| 19. Flow meter SR 356 | R03-0346 |
| 20. Steel net disc SR 336 | T01-2001 |
| 21. Asbestos Kit SR 509 | T06-0105 |
| 22. Battery SR 501, 2,25 Ah | R06-0108 |
| 22. Battery HD SR 502, 3,5 Ah | T06-0101 |
| 23. Battery charger | R06-0433 |
| 23. Battery charger (UK ONLY) | R06-0435 |
| 23. Battery charger (AUS ONLY) | R06-0436 |
| 24. Charging station without chargers SR 506 | T06-0108 |
| 24. Charging station, complete SR 516 | T06-0111 |
| 25. Belt SR 508 | R06-0101 |
| 25. Rubber belt SR 504 | T06-0104 |
| 25. PVC belt | T06-0124 |
| 26. Leather belt SR 503 | T06-0103 |
| 26. Leather belt SR 503, large | T06-0107 |
| 27. HD belt SR 553, standard | T06-0119 |
| 27. HD belt SR 553, large | T06-0120 |
| 28. Harness SR 552 | T06-0116 |
| 29. Fan SR 500, bare | R06-0110 |
| 30. Splash cover SR 514 | T06-0114 |
| 31. Storage bag SR 505 w two compartments | T06-0102 |
| 32. Pre-filter holder SR 512 | R06-0106 |
| 33. Pre-filter SR 221 | H02-0312 |
| 34. Particle filter P3 R, SR 510 | H02-1312 |
| 35. Filter adapter SR 511 | R06-0105 |
| 36. Pre-filter holder for SR 710 | R01-0605 |
| 37. Particle filter P3 R, SR 710 | H02-1512 |
| 38. Gas filter A2, SR 518 | H02-7012 |
| 39. Gas filter ABE1, SR 515 | H02-7112 |
| 40. Gas filter A1BE2K1, SR 597 | H02-7212 |
| 41. Combined filter A1BE2K1-Hg-P3 R, SR 599 | H02-7312 |
| 42. Gasket for fan | R06-0107 |
| 43. Plug kit | R06-0703 |

