ARDON®
WORKWEAR
& OUTDOOR

ARDON®ULTRITE®S3S

SAFETY SHOES







DRY AIR



REFLECTIVE



WATER REPELLENT



DEFUSE CONTROL

TECHNICAL SHEET

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON® ULTRITE® S3S

SAFETY SHOES



ARTICLE	**G3524, G3526**
COLOR	**Green, Black**
Material	
Upper	Split nubuck leather + TPU
Lining	Sandwich textile
Outsole	Rubber
Toe cap	Fiberglass
Midsole	Kevlar
Insole	Knit mesh with PU
SIZES	36-48, 35-50
UNIT	Pair
PACKAGING	
Units in a carton	10 pairs
Units in a box	1 pair

DIMENSIONS	35-43	44-50
Carton D x H x W (cm)	33,5 x 51,5 x 61,5	38,5 x 53,5 x 66,5
Carton (cbm)	0,1061	0,1369

Size EUR	**35**	**36**	**37**	**38**	**39**	**40**	**41**	**42**	**43**	**44**	**45**	**46**	**47**	**48**	**49**	**50**
Insole length mm	230	237	244	250	257	264	270	277	284	290	297	304	310	317	324	329
Foot length cm	22,0	22,7	23,4	24,0	24,7	25,4	26,0	27,0	27,4	28,0	28,7	29,4	30,0	30,7	31,4	31,9

DESCRIPTION

Safety ankle boots with a split nubuck leather upper combined with TPU for universal use. Toe protection is provided by a durable fiberglass toe cap, and the heel is stabilized by a TPU protector. The rubber outsole provides high comfort, excellent traction, and stability for indoor and outdoor wear.

TECHNICKÝ LIST

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

NORMS

(EU) 2016/425
EN ISO 20345:2022+A1:2024 Personal protective equipment - Safety footwear

Category: S3S SR FO HRO SC CI HI LG

Categories	**EN ISO 20345**	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SR - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	SR
WPA - upper resistant to water	✓	WPA
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
The shoes do not contain metal parts		0% METAL
HRO - resistance to contact heatup to 300 °C	✓	300 °C
insulation of the bottom of the shoe against heat	✓	HI
insulation of the bottom of the shoe against the cold	✓	CI
Splatters of molten metal		WG
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		ESD
LG - ladder grip, footware provides extra grip on ladder rungs	✓	LG

TECHNICAL SHEET

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON®
WORKWEAR
& OUTDOOR



CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3524/36	8592390416254	13,48	1,348
G3524/37	8592390416261	13,96	1,396
G3524/38	8592390416278	14,48	1,448
G3524/39	8592390416285	14,90	1,490
G3524/40	8592390416292	15,22	1,522
G3524/41	8592390416308	16,05	1,605
G3524/42	8592390416315	16,82	1,682
G3524/43	8592390416322	17,40	1,740
G3524/44	8592390416339	18,10	1,810
G3524/45	8592390416346	18,60	1,860
G3524/46	8592390416353	19,06	1,906
G3524/47	8592390416360	19,72	1,972
G3524/48	8592390416377	20,04	2,004
G3526/35	8592390416780	13,00	1,3
G3526/36	8592390416797	13,48	1,348
G3526/37	8592390416803	13,96	1,396
G3526/38	8592390416810	14,48	1,448
G3526/39	8592390416827	14,90	1,490
G3526/40	8592390416834	15,22	1,522
G3526/41	8592390416841	16,05	1,605
G3526/42	8592390416858	16,82	1,682
G3526/43	8592390416865	17,40	1,740
G3526/44	8592390416872	18,10	1,810
G3526/45	8592390416889	18,60	1,860
G3526/46	8592390416896	19,06	1,906
G3526/47	8592390416902	19,72	1,972
G3526/48	8592390416919	20,04	2,004
G3526/49	8592390416926	21,06	2,106
G3526/50	8592390416933	21,66	2,166

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON®
WORKWEAR
& OUTDOOR





© ARDON.s.r.o. / ALL RIGHTS RESERVED

ARDON®
WORKWEAR
& OUTDOOR







TECHNICAL SHEET

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz