ARDON®VALI S2 ESD

SAFETY SHOES

TECHNICAL SHEET



DRY AIR

WASH-FRIENDLY

ZIPPERS

ESD

© ARDON s.r.o. / ALL RIGHTS RESERVED

ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON®VALI S2 ESD

SAFETY SHOES



ARTICLE	**G1266**

MATERIAL

Upper	MICROFIBER with a thicknessof 1,6 mm
Lining	MESH laminated breathable fabric
Sole	PU/PU, two-component spray coating, oil resistant, anti-static, antislip
Toe cap	steel 459
Plate	-
Insole	BASIC

SIZE	36-48
UNIT	pair

PACKAGE

Units in a carton	10 pairs
Units in a box	1 pair

DIMENSIONS	36-42	43-48
Carton H x W x D (cm)	61 x 33,5x 40,5	64,5x 35,5 x 42,5
Carton (cbm)	0,0828	0,0973

Size EUR	**35**	**36**	**37**	**38**	**39**	**40**	**41**	**42**	**43**	**44**	**45**	**46**	**47**	**48**	**49**	**50**	**51**
Insole length mm	-	234	241	247	254	261	267	274	281	287	294	301	307	314	-	-	-
Foot length cm	-	22,9	23,6	24,2	24,9	25,6	26,2	26,9	27,6	28,2	28,9	29,6	30,2	30,9	-	-	-

DESCRIPTION

White safety moccasin with microfiber upper and steel toe cap. Two-component polyurethane sole with the highest level of anti-slip protection.

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

NORMS

(EU) 2016/425
EN ISO 20345:2011 Personal protective equipment - Safety footwear
EN IEC 61340-4-3:2018 Electrostatics: Standard test methods for specific application – Footwear

Category S2 SRC ESD

Categories	**EN ISO 20345**	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	SRC
WR - upper resistant to water	✓	
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)		
SRA - slip resistance ceramic floor tiles with SLS		SRA
HRO - resistance to contact heatup to 300 °C		300 °C
HI-insulation of the bottom of the shoe against heat		HI
CI-insulation of the bottom of the shoe against the cold		CI
Splatters of molten metal		WG
ESD – shoe protects against electrostatic discharge and can be used on EPA premises	✓	ESD
The shoes do not contain metal parts		0% METAL
-		
-		
-		

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G1266/36	8592390061232	10.6	1.06
G1266/37	8592390061249	10.8	1.08
G1266/38	8592390061256	11,0	1.10
G1266/39	8592390061263	11.2	1.12
G1266/40	8592390061270	11.6	1.16
G1266/41	8592390061287	11.8	1.18
G1266/42	8592390061294	12,0	1.20
G1266/43	8592390061300	12.2	1.22
G1266/44	8592390061317	12.8	1.28
G1266/45	8592390061324	13.1	1.31
G1266/46	8592390061331	13.5	1.35
G1266/47	8592390061348	13.8	1.38
G1266/48	8592390061355	14.1	1.41



© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON®
WORKWEAR
& OUTDOOR



© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON®
WORKWEAR
& OUTDOOR







© ARDON s.r.o. / ALL RIGHTS RESERVED